



Dávkovacie čerpadlá - Tekna model TPG, TPR, AKS

Technické údaje:

TEKNA typ:	max. prietok lit./h	max. výtlak bar	max. počet kmitov / minúta	ovládanie	napojenie vst./výst. mm
AKS 603 PVC, 230V50Hz	8	12	160	analógové	4/6 – 4/6
AKS 603 PVDF, 230V50Hz	8	12	160	analógové	4/6 – 4/6
TPG 500 PVC, 230V50Hz	1,5	20	120	digitálne	4/6 – 4/7
TPG 500 PVDF, 230V50Hz	1,5	20	120	digitálne	4/6 – 4/7
TPG 603 PVC, 230V50Hz	8	12	160	digitálne	4/6 – 4/6
TPG 603 PVDF, 230V50Hz	8	12	160	digitálne	4/6 – 4/6
TPR 603 PVC, 230V50Hz	8	12	160	digitálne - pH	4/6 – 4/6
TPR 603 PVDF, 230V50Hz	8	12	160	Digitálne - pH	4/6 – 4/6



Tekna AKS

	bar	lit./h	kmit/min.	ml/kmit
Typ 500	20	0,4	120	0,06
	16	0,8		0,11
	10	1,2		0,17
	6	1,5		0,21
Typ 600	20	2,5	120	0,35
	18	3		0,42
	14	4,2		0,58
	8	7		0,97
Typ 603	12	4	160	0,42
	10	5		0,52
	8	6		0,63
	2	8		0,83
Typ 800	16	7	300	0,39
	10	10		0,56
	5	15		0,83
	1	18		1,00
Typ 800	5	20	300	1,11
	4	25		1,39
	2	38		2,11
	0,1	54		3,00



Tekna TPG, TPR

poznámky:

TPR **neobsahuje pH sondu**